



# THR.400.A4D

MADE IN ITALY



TH400 - In-line circular joint connector type "I" IP68

KIT

**IP68**



## GENERAL DESCRIPTION

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEETUBE® - In-line and junction circular connectors IP68/IP69K
Product name (Series)	TH400 - Giunto circolare di connessione lineare tipo "I" IP68
Product configuration	In-line joint connector
Type of Fixation	With quick-fix mounting clip <small>* Mounting clip to be ordered separately (code 6000302CC).</small>
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 32 mm x 130 mm

## ELECTRICAL CHARACTERISTICS

Number of poles	4
Contact marking	1 - 2 - 3 - 4
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 32A
Operating voltage	max. 450V AC

Contact our Customer Service for availability of other markings.

## MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (50m,1h)/IP69K
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

## CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm <sup>2</sup> - 4.0 mm <sup>2</sup>
Wire cross-section min. - max. (Solid cable)	0.5 mm <sup>2</sup> - 4.0 mm <sup>2</sup>
Cable diameter min. - max.	6.0 mm - 17.0 mm <small>* Accessories e riduzioni per cavi incluse nella confezione.</small>

## MATERIAL CHARACTERISTICS

Body	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free
T marking	T 85°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 250



**i** Contact our Customer Service for more information on additional tests and approvals.

#### INDUSTRY STANDARDS

**Standard number** EN 60998-1:2004

#### PACKAGING INFORMATION

**Packaging method** single packed unit

**Quantity (product/bag)** 1 product/bag

**Quantity (product/box)** 50 bags/box

**Unit weight** 103,1 gram/bag

**Box dimension** 400 x 230 x 400

**i** Accessories and installation instructions included in the kit.

#### INSTALLATION INSTRUCTIONS

- IST TH390I-400I v01 techno PDF • 924 KB
- Guidelines Installation PDF • 753 KB

#### CERTIFICATIONS AND TEST REPORTS

- CE-TH400 DOC • 142 KB
- TEETUBE CA0201889-I-2085 PDF • 3 MB

#### MARKETING COLLATERALS

- Cameriere pag intera PDF • 2 MB
- pannello techno 04 vert 80x120 LOW  
PDF • 633 KB

#### DRAWINGS

- THB400D1ASTEP  
• 2 MB • CONFIDENTIAL DOCUMENT